

CBB CL型

CBB



技术要求

参照标准	IEC 60384-2, GB 7332	额定电压(U)	20℃ U=1.0UR,2s	说明
气候类别	55/125/21	电容量偏差	20℃ U=1.0UR,2s	①、额定电压中的交流电压的频率是工频(50Hz) 电容量在工作电压频率上升而下降; ②、电容器的电压随温度上升而下降;在85-100℃之间,以85℃为标准,环境温度每上升1℃,电容量在工作电压频率上升而下降; ③、电容器的额定工作电压应降在1.25%。 ④、以上注意事项在使用电容器时应充分考虑。
额定温度(T)	85℃			
额定电压(U)	63Vdc/40Vac, 100Vdc/63Vac, 160Vdc/30Vac, 250Vdc/160Vac, 400Vdc/250Vac, 630Vdc/320Vac			
电容量(CR)范围	0.001~47μF			
电容量偏差	20℃, 1KHz ±5% (I), ±20% (M)	损耗角正切tgδ	20℃ 18Hz, tgδ≤0.0070 100Hz, tgδ≤0.0100 (CR≤1μF) 100KHz, tgδ≤0.0100 (CR≥1μF)	

额定电压	630Vdc/220Vac					630Vdc/220Vac					630Vdc/220Vac				
	外形尺寸					外形尺寸					外形尺寸				
标准容量	Wmax	Hmax	Tmax	P	d	Wmax	Hmax	Tmax	P	d	Wmax	Hmax	Tmax	P	d
(μF)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
0.0010	7.2	7.0	4.0	5.0	0.5	10.2	7.5	3.5	7.5	0.6					
0.0012	7.2	7.0	4.0	5.0	0.5	10.2	7.5	3.5	7.5	0.6					
0.0015	7.2	7.0	4.0	5.0	0.5	10.2	7.5	3.5	7.5	0.6					
0.0018	7.2	7.0	4.0	5.0	0.5	10.2	7.5	3.5	7.5	0.6					
0.0022	7.2	7.0	4.0	5.0	0.5	10.2	7.5	3.5	7.5	0.6					
0.0027	7.2	7.0	4.0	5.0	0.5	10.2	7.5	3.5	7.5	0.6	13.0	8.5	4.0	10.0	0.6
0.0033	7.2	7.0	4.0	5.0	0.5	10.2	7.5	3.5	7.5	0.6	13.0	9.0	4.0	10.0	0.6
0.0039	7.2	7.0	4.0	5.0	0.5	10.2	7.5	3.5	7.5	0.6	13.0	9.0	4.0	10.0	0.6
0.0047						10.2	7.5	3.5	7.5	0.6	13.0	9.0	4.0	10.0	0.6
0.0056						10.2	7.5	3.5	7.5	0.6	13.0	9.0	4.0	10.0	0.6
0.0068						10.2	7.5	3.5	7.5	0.6	13.0	9.0	4.0	10.0	0.6
0.0082						10.2	7.5	3.5	7.5	0.6	13.0	9.0	4.0	10.0	0.6
0.0100						10.2	8.0	4.0	7.5	0.6	13.0	9.0	4.0	10.0	0.6
0.0120						10.2	8.0	4.0	7.5	0.6	13.0	9.0	4.0	10.0	0.6
0.0150						10.2	8.5	4.5	7.5	0.6	13.0	9.0	4.0	10.0	0.6
0.0180						10.2	9.0	5.0	7.5	0.6	13.0	9.0	4.0	10.0	0.6
0.0220						10.2	9.5	5.5	7.5	0.6	13.0	9.0	4.5	10.0	0.6
0.0270											13.0	9.5	5.0	10.0	0.6
0.0330											13.0	10.0	5.5	10.0	0.6
0.0390											13.0	10.5	5.5	10.0	0.6
0.0470											13.0	11.0	6.0	10.0	0.6
0.0560											13.0	11.5	7.0	10.0	0.6
0.0680											13.0	12.0	7.5	10.0	0.6



额定电压	630Vdc/220Vac					630Vdc/220Vac					630Vdc/220Vac				
	外形尺寸					外形尺寸					外形尺寸				
标准容量	Wmax	Hmax	Tmax	P	d	Wmax	Hmax	Tmax	P	d	Wmax	Hmax	Tmax	P	d
(μF)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
0.010	18.0	10.0	4.5	15.0	0.6										
0.012	18.0	10.0	4.5	15.0	0.6										
0.015	18.0	11.5	4.5	15.0	0.6										
0.018	18.0	12.0	4.5	15.0	0.6										
0.022	18.0	12.0	4.5	15.0	0.6										
0.027	18.0	12.0	4.6	15.0	0.6										
0.033	18.0	12.0	4.5	15.0	0.6										
0.039	18.0	12.0	5.0	15.0	0.6										
0.047	18.0	12.0	5.0	15.0	0.6	26.5	15.0	6.0	22.5	0.8					
0.056	18.0	12.0	5.0	15.0	0.6	26.5	15.0	6.0	22.5	0.8					
0.068	18.0	12.0	5.0	15.0	0.6	26.5	15.0	6.0	22.5	0.8	32.0	16.0	6.0	27.5	0.8
0.082	18.0	12.5	5.5	15.0	0.6	26.5	15.0	6.0	22.5	0.8	32.0	16.0	6.0	27.5	0.8
0.100	18.0	13.0	6.0	15.0	0.8	26.5	15.0	6.0	22.5	0.8	32.0	16.0	6.0	27.5	0.8
0.120	18.0	13.5	6.5	15.0	0.8	26.5	15.0	6.0	22.5	0.8	32.0	16.0	6.0	27.5	0.8
0.150	18.0	14.5	7.5	15.0	0.8	26.5	16.0	6.0	22.5	0.8	32.0	16.0	6.0	27.5	0.8
0.180	18.0	15.0	8.0	15.0	0.8	26.5	16.0	6.0	22.5	0.8	32.0	16.0	6.0	27.5	0.8
0.220	18.0	16.0	9.0	15.0	0.8	26.5	16.5	6.0	22.5	0.8	32.0	16.0	6.0	27.5	0.8
0.270	18.0	17.0	10.0	15.0	0.8	26.5	17.0	6.5	22.5	0.8	32.0	16.0	6.0	27.5	0.8
0.330						26.5	17.5	7.5	22.5	0.8	32.0	17.0	6.5	27.5	0.8
0.390						26.5	18.5	8.0	22.5	0.8	32.0	17.5	7.0	27.5	0.8
0.470						26.5	19.5	9.0	22.5	0.8	32.0	18.0	8.0	27.5	0.8
0.560						26.5	20.5	10.0	22.5	0.8	32.0	19.0	9.0	27.5	0.8
0.680						26.5	21.5	11.5	22.5	0.8	32.0	20.0	10.0	27.5	0.8
0.820						26.5	23.0	12.5	22.5	0.8	32.0	21.0	11.0	27.5	0.8
1.000						26.5	24.5	14.0	22.5	0.8	32.0	22.5	12.0	27.5	0.8
1.200											32.0	24.0	13.5	27.5	0.8
1.500											32.0	26.0	15.5	27.5	0.8
1.800											32.0	27.5	17.0	27.5	0.8
2.200											32.0	29.5	19.0	27.5	0.8

封装:
阻燃粉末环氧
树脂封装,阻
燃性达UL94-
V0级环保型;
符合标准